

# United States Patent and Trademark Office

y

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/970,611	10/03/2001	Dwight Poplin	10004192-1	2702
57299	7590 10/06/2006		EXAMINER	
AVAGO T	ECHNOLOGIES, LTD.	JERABEK, KELLY L		
P.O. BOX 1920 DENVER, CO 80201-1920			ART UNIT	PAPER NUMBER
,			2622	
			DATE MAILED: 10/06/2006	

Please find below and/or attached an Office communication concerning this application or proceeding.

·	Application No.	Applicant(s)
	09/970,611	POPLIN, DWIGHT
Office Action Summary	Examiner	Art Unit
	Kelly L. Jerabek	2622
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA  - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period v  - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be timused and will expire SIX (6) MONTHS from a cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).
Status	•	
<ul> <li>1) Responsive to communication(s) filed on 19 July</li> <li>2a) This action is FINAL. 2b) This</li> <li>3) Since this application is in condition for alloward closed in accordance with the practice under Exercise.</li> </ul>	action is non-final.	
Disposition of Claims		
4) ☐ Claim(s) 1,3-8,10,12-16 and 18-23 is/are pend 4a) Of the above claim(s) is/are withdraw 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1, 3-8, 10, 12-16 and 18-23 is/are rejee 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or	vn from consideration. ected. r election requirement.	
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) accomplicated any not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examine	epted or b) objected to by the I drawing(s) be held in abeyance. See ion is required if the drawing(s) is ob	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
<ul> <li>12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents</li> <li>2. Certified copies of the priority documents</li> <li>3. Copies of the certified copies of the priority application from the International Bureau</li> <li>* See the attached detailed Office action for a list</li> </ul>	s have been received. s have been received in Applicati rity documents have been receive u (PCT Rule 17.2(a)).	on No ed in this National Stage
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4)	ate
3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date	6) Other:	atom rippiloution

Art Unit: 2622

### **DETAILED ACTION**

## Continued Examination Under 37 CFR 1.114

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 6/19/2006 has been entered.

# Claim Rejections - 35 USC § 112

The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claims 1, 3-8, 10, 12-16 and 18-23 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. Independent claims 1,

10 and 18 disclose processing raw image data using first and second settings being performed substantially in parallel and **without user interaction**. The Examiner can find no support in the original disclosure for the limitation that processing raw image data using first and second settings is performed **without user interaction**.

# Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1, 3-8, 10, 12-16, and 18-23 rejected under 35 U.S.C. 103(a) as being unpatentable over Shinsky et al. US 6,285,398 in view of Nortia et al. US 2004/0169767.

Re claim 18, Shinsky discloses in figure 3 a system including a video camera capable of transmitting raw video data to a host computer where it is processed and converted for display (col. 4, lines 6-27). The system provides a method of adjusting image-capturing parameters of an image-capturing device (100) comprising: capturing a scene of interest as raw image data using an image sensor (12) of the image-capturing

Art Unit: 2622

device (100) (col. 4, lines 30-53); processing the raw image data using first settings of the image capturing parameters (contrast, brightness, hue, gain, etc.) to produce a first image of the scene of interest; processing the raw image data using second settings of the image capturing parameters (contrast, brightness, hue, gain, etc.) to produce a second image of the scene of interest (col. 5, line 31- col. 8, line 35; col. 9, line 40 - col. 10, line 65) (The host computer (200) processes the raw image data in order to continually adjust the gain and appropriately adjust the control signals according to input of a user via a graphical user interface, thus multiple images are produced according to the updated image capturing parameters); and adjusting current settings of the image capturing parameters of the image capturing device (100) to conform with one of the first and second images, the adjusted current settings of the image capturing parameters being used by the image capturing device (100) to capture a subsequent image (generated shutter and AGC control signals are provided to the camera (100) (col. 8, lines 1-15, 55-67)). Although the Shinsky reference discloses all of the above limitations including a graphical user interface allowing a user view images and to provide control inputs to adjust current settings (gain value, contrast, brightness, hue, etc.) of a picture, the reference fails to distinctly state that first and second images having different image capturing parameters are displayed for user selection and the current settings of the image capturing parameters are adjusted to conform with one of the first and second images selected by a user.

Norita discloses in figure 9 a flow chart of the operation of manual exposure photography of a digital camera. The camera includes an image sensor (9) that

Art Unit: 2622

captures a plurality of images at different exposure times by activating after a lapse of time (Ti) and replacing the previous image signal in a buffer memory (82) with the current image signal (page 6, paragraphs 115-118). Therefore, a first image and a second image are captured using different settings of image-capturing parameters (exposure settings). Each of the images corresponding to a different exposure setting is displayed on an LCD (51), and when an image with desired exposure is displayed on the LCD (51) a user selects that image by pressing a release button (30) (page 6, paragraphs 119-120). Therefore, first and second images corresponding to different exposure settings are displayed as comparison images for user selection. The exposure settings of the camera are changed for each exposure time in order to obtain images of varying exposure (page 6, paragraphs 118-119). Therefore, the current settings of the image capturing parameters (exposure settings) are adjusted for each image that is written to the buffer memory (82). If the user presses the release button (30), the process goes on to step 45 and the exposure is not further changed (page 6, paragraphs 120-121). Since when the release button is pressed the exposure time is not further changed (and the exposure time is changed otherwise) the Examiner is reading this feature as adjusting current settings (corresponding to not changing the exposure time) of the image-capturing parameters of the image-capturing device. Therefore, the current settings of the image capturing parameters remain the same when an image is selected by a user. Thus, the settings conform with the image selected by the user. As stated above, Norita discloses a method of displaying comparison images for user selection and subsequently adjusting settings of an image

Page 5

Art Unit: 2622

capturing device according to the user selection. Therefore, it would have been obvious for one skilled in the art to have been motivated to include the concept of adjusting the currents settings of image capturing parameters according to a displayed image that is selected by a user as disclosed by Norita in the method of processing raw image data by setting image capturing parameters using a graphical user interface as disclosed by Shinsky. Doing so would provide a means for specifying an image having proper image capturing parameters while viewing a serially updated image in order to set the image capturing parameters (Norita: page 7, paragraph 135).

Re claim 19, the image capturing parameters adjusted by the host computer (200) include contrast, brightness, hue, gamma correction, and white balance (col. 6, lines 17-35; col. 7, lines 57-60; col. 9, lines 44-48).

Re claim 20, Norita states that the LCD (51) can display images either in sequence or in parallel after photo shooting (page 6, paragraph 124). Therefore, first and second images corresponding to different exposure settings may be simultaneously displayed.

Re claim 21, Norita states that the LCD (51) can display images either in sequence or in parallel after photo shooting (page 6, paragraph 124). Therefore, first and second images corresponding to different exposure settings may be sequentially displayed.

Re claim 1, Shinsky discloses in figure 3 a system including a video camera capable of transmitting raw video data to a host computer where it is processed and converted for display (col. 4, lines 6-27). The system provides a method of adjusting image-capturing parameters of an image-capturing device (100) comprising: a first image and a second image using different settings of image capturing parameters including: processing raw image data using first settings of the image capturing parameters (contrast, brightness, hue, gain, etc.) to produce a first image of the scene of interest; processing the raw image data using second settings of the image capturing parameters (contrast, brightness, hue, gain, etc.) to produce a second image of the scene of interest (col. 4, lines 30-53;col. 5, line 31- col. 8, line 35; col. 9, line 40 – col. 10, line 65) (The host computer (200) processes the raw image data in order to continually adjust the gain and appropriately adjust the control signals according to input of a user via a graphical user interface, thus multiple images are produced according to the updated image capturing parameters); and adjusting current settings of the image capturing parameters of the image capturing device (100) to conform with one of the first and second images, the adjusted current settings of the image capturing parameters being used by the image capturing device (100) to capture a subsequent image (generated shutter and AGC control signals which conform to the user input via the graphical user interface are provided to the camera (100) (col. 8, lines 1-15, 55-67)). Although the Shinsky reference discloses all of the above limitations including a graphical user interface allowing a user view images and to provide control inputs to

Art Unit: 2622

adjust current settings (gain value, contrast, brightness, hue, etc.) of a picture, the reference fails to distinctly state that first and second images having different image capturing parameters are displayed for user selection and the current settings of the image capturing parameters are adjusted to conform with one of the first and second images selected by a user .

Norita discloses in figure 9 a flow chart of the operation of manual exposure photography of a digital camera. The camera includes an image sensor (9) that captures a plurality of images at different exposure times by activating after a lapse of time (Ti) and replacing the previous image signal in a buffer memory (82) with the current image signal (page 6, paragraphs 115-118). Therefore, a first image and a second image are captured using different settings of image-capturing parameters (exposure settings). Each of the images corresponding to a different exposure setting is displayed on an LCD (51), and when an image with desired exposure is displayed on the LCD (51) a user selects that image by pressing a release button (30) (page 6. paragraphs 119-120). Therefore, first and second images corresponding to different exposure settings are displayed as comparison images for user selection. The exposure settings of the camera are changed for each exposure time in order to obtain images of varying exposure (page 6, paragraphs 118-119). Therefore, the current settings of the image capturing parameters (exposure settings) are adjusted for each image that is written to the buffer memory (82). If the user presses the release button (30), the process goes on to step 45 and the exposure is not further changed (page 6, paragraphs 120-121). Since when the release button is pressed the exposure time is

not further changed (and the exposure time is changed otherwise) the Examiner is reading this feature as adjusting current settings (corresponding to not changing the exposure time) of the image-capturing parameters of the image-capturing device. Therefore, the current settings of the image capturing parameters remain the same when an image is selected by a user. Thus, the settings conform with the image selected by the user. As stated above, Norita discloses a method of displaying comparison images for user selection and subsequently adjusting settings of an image capturing device according to the user selection. Therefore, it would have been obvious for one skilled in the art to have been motivated to include the concept of adjusting the currents settings of image capturing parameters according to a displayed image that is selected by a user as disclosed by Norita in the method of processing raw image data by setting image capturing parameters using a graphical user interface as disclosed by Shinsky. Doing so would provide a means for specifying an image having proper image capturing parameters while viewing a serially updated image in order to set the image capturing parameters (Norita: page 7, paragraph 135).

Re claim 3, the step of capturing first and second images includes sequentially capturing a scene of interest using two different settings of a selected image capturing parameter to capture the first and second images (an automatic exposure algorithm is performed in order to generate shutter and AGC control signals to ensure that the proper signal level is output from the camera (100). The automatic exposure algorithm

Art Unit: 2622

is operated continuously in order to produce updated control signals at intervals of every ten frames (col. 8, lines 1-15).

Re claim 4, the image capturing parameters adjusted by the host computer (200) include contrast, brightness, hue, gamma correction, exposure period, and white balance (col. 6, lines 17-35; col. 7, lines 57-60; col. 8, lines 1-15; col. 9, lines 44-48).

Re claim 5, see claim 4.

Re claim 6, Norita states that the LCD (51) can display images either in sequence or in parallel after photo shooting (page 6, paragraph 124). Therefore, first and second images corresponding to different exposure settings may be simultaneously displayed.

Re claim 7, Norita states that the LCD (51) can display images either in sequence or in parallel after photo shooting (page 6, paragraph 124). Therefore, first and second images corresponding to different exposure settings may be sequentially displayed.

Re claim 8, a subsequent (third) image is captured using the current settings (calculated shutter, AGC, and gain adjustment values) of the image capturing parameters to produce the third image (col. 8, line 57 – co. 9, line 37).

Re claim 22, the image capturing parameters adjusted by the host computer (200) include contrast, brightness, hue, gamma correction, and white balance (col. 6, lines 17-35; col. 7, lines 57-60; col. 9, lines 44-48).

Re claim 10, see claim 1.

Re claim 12, see claim 3.

Re claim 13, see claim 4.

Re claim 14, see claim 5.

Re claim 15, see claim 6.

Re claim 16, see claim 7.

Re claim 23, the image capturing parameters adjusted by the host computer (200) include contrast, brightness, hue, gamma correction, and white balance (col. 6, lines 17-35; col. 7, lines 57-60; col. 9, lines 44-48).

Art Unit: 2622

## Contacts

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kelly L. Jerabek whose telephone number is (571) 272-7312. The examiner can normally be reached on Monday - Friday (8:00 AM - 5:00 PM).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Vivek Srivastava can be reached on (571) 272-7304. The fax phone number for submitting all Official communications is (703) 872-9306. The fax phone number for submitting informal communications such as drafts, proposed amendments, etc., may be faxed directly to the Examiner at (571) 273-7312.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). KLJ

KLJ

Welly L.J.

VIVEK SRIVASTAVA
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600

Page 12